

FTTH Drop Cable Type Fiber Optic Splice & Splitter Closure



Description:

FTTH Drop Cable Type Fiber Optic Splice & Splitter Closure features with ruggedness, which is tested under harsh conditions and stand up to even the most severe conditions of moisture, vibration and extreme temperatures. Humanized design helps user get better experience and safer operating environment.

Features:

- Dis-mountable adaptor panel
- Support midspan termination
- Easy operation and installation
- Rotatable and dis-mountable splice tray for easy splicing

Applications:

- Wall mounting & pole mounting installation
- Suitable for 2*3mm Indoor FTTH Drop Cable and Outdoor Figure 8 FTTH Drop Cable (standard) or 6mm cable (optional)

Specification:

Model	F2H-JCD-24-I2	F2H-JCD-16-I4		F2H-JCD-24-I4	
Adapter	24pcs of SC	16pcs of SC		24pcs of SC	
Cable Ports	1 uncut port	1 uncut port	2 round ports	1 uncut port	2 round ports
Applicable Cable Diameter	10~17.5mm	10~17.5mm	8~17.5mm	10~17.5mm	8~17.5mm
Drop Cable Ports	24 ports	16 ports		24 ports	
Applicable Cable Diameter	2*3mm FTTH Drop Cable, 2*5mm Figure 8 FTTH Drop Cable, 6mm cable (optional)				
Dimension	385*245*130mm	385*245*130mm		385*245*155mm	
Material	modified polymer plastic				
Sealing Structure	mechanical sealing				
Color	black				
Maximum Splicing Capacity	48 fibers (4 trays, 12 fibers/tray)				
Applicable Splitter	1pc of 1*16 PLC Splitter or 2pcs of 1*8 PLC Splitters				
Sealing	IP68				
Impact Test	IK10				
Pull Force	100N				

Midspan Entry	yes
Storage (Tube/Micro Cable)	yes
Net Weight	4kg
Gross Weight	5kg
Packing	540*410*375mm (4pcs per carton)