

OLT EPON 16 PON Pizza-Box



DESCRIPCION

OLT EPON 16 PON + SFP

MODELO

FD1216S-R1 DAP

CODIGO WT

4281355

Casa Central

Domingo French 831, B1603BNI, Villa Martelli, BS AS, Argentina
Tel:(54) 011-4709-6650
ventas@wiretechsa.com.ar

Sucursal Córdoba

Diaguitas 3138, Córdoba, CP 5008, Argentina
Te:(54) 0351 476-1313 – 0908
sucursalcordoba@wiretechsa.com.ar

1 - CARACTERISTICAS

- ❖ FD1216S-R1 Producto de montaje en rack de 19 pulgadas de 1U de altura. Las características del OLT son pequeñas, convenientes, flexible, fácil de implementar, de alto rendimiento. Compacta.
- ❖ El OLT se puede utilizar para aplicaciones de "Triple-Play", CPN, cámara IP, LAN empresarial e IOT. Es un productos de alto rendimiento.
- ❖ FD1208S-R1 proporciona 1 interfaz USB, interfaz óptica 4GE (cobre) y 4GE, enlace ascendente de 4 * 10 Gb.
- ❖ Interfaz y 16 puertos EPON para flujo descendente. Puede admitir 1024 ONU con una relación de divisor de 1:64.

2 – ESPECIFICACIONES

Item		FD1216S-R1
Chassis	Rack	1U 19 inch standard box
Uplink Port	QTY	10
	Copper	10/100/1000M auto-negotiable,RJ45:4pcs
	Optical interface	4 GE
	10Gb uplink interface	2*10Gb
PON Port	QTY	16
	Physical Interface	SFP Slots
	Connector Type	1000BASE-PX20+
	Max splitting ratio	1:64
USB Port	QTY	1
	Connector Type	TYPE-C
Management Ports		1*100BASE—TX outband port; 1CONSOLE port
PON Port Specification (Apply to C-Data PON module)	Transmission Distance	20KM
	PON port speed	Symmetrical 1.25Gbps
	Wavelength	1490nm TX,1310nm RX
	Connector	SC/PC
	Fiber Type	9/125µm SMF
	TX Power	+2.5~+7dBm
	Rx Sensitivity	-27dBm
	Saturation Optical Power	-6dBm
10Gb SFP+ Port Specification (Apply to C-Data 10Gb)	Transmission Distance	10KM
	PON port speed	8.5-10.51875Gbps
	Wavelength	1310nmTX, 1310nmRX
	Connector	LC

3 – ESPECIFICACIONES

module)	Fiber Type	Single mode with dual fiber
	TX Power	-8.2~+0.5 dBm
	Rx Sensitivity	-12.6dBm
Management Mode		SNMP, Telnet, CLI management mode.
Management Function		Fan Group Detecting Port Status monitoring and configuration management; Layer-2 switch configuration such as Vlan, Trunk ,RSTP,IGMP ,QOS, etc; EPON management function: DBA ,ONU authorization, ACL ,QOS ,etc; Online ONU configuration and management User management Alarm management
Layer-two Switch		Support port Vlan and protocol Vlan Support Vlan tag/Untag ,vlan transparent transmission; Support 4096 VLAN Support 802.3dd trunk RSTP QOS based on port ,VID,TOS and MAC address IGMP Snooping 802.x flow control Port stability statistic and monitoring
EPON Function		Support port-based rate limitation and bandwidth control; In compliant with IEEE802.3ah Standard Up to 20KM transmission Distance Support data encryption, group broadcasting, port Vlan separation, RSTP, etc. Support Dynamic Bandwidth Allocation (DBA) Support ONU auto-discovery/Link detection/remote upgrade of software; Support VLAN division and user separation to avoid broadcast storm; Support various LLID configuration and single LLID configuration .Different user and different service could provide different QoS by means of different LLID channels. Support power-off alarm function ,easy for link problem detection Support broadcasting storm resistance function Support port isolation between different ports Support ACL and SNMP to configure data packet filter flexibly Specialized design for system breakdown prevention to maintain stable system Support dynamic distance calculation on EMS online Support RSTP,IGMP Proxy
Layer-three Route		Support static unicast Support static multicast Support RIP routing protocol Support dynamic multicast protocol with active source
Backplane Bandwidth		88G
Dimension		440*350*44(mm*mm*mm)
Weight		6kg
Power Supply	220VAC	AC: 90V~240V, 47/63Hz
	-48DC	DC:-36V~-72V
Power Consumption		70W
Operating Environment	Working Temperature	0~50℃
	Storage Temperature	-40~85℃
	Relative Humidity	5~90%(non-condensing)